

## • HH2681 Aqueous hyperdispersant

It is a water-based dispersant suitable for wet grinding of organic and inorganic powders without resin dispersion.

## • Product Data

### Composition:

High molecular weight water-based acrylic copolymer containing carboxyl groups.

### Typical Properties:

Appearance: light yellow liquid

PH value: 7-8

Solid content: 40%

Solvent: water

Viscosity: 60 seconds (coated 4# cup) (25°C)

Ionic properties: anionic

Type: HH2681

\*.The values indicated in this data sheet describe typical properties and do not constitute specification limits.

## • Applications

### Special Features and Benefits:

Used to produce high-solid and low-viscosity liquid slurry, excellent tinting strength, good color paste storage stability. No VOC.

## • Recommended Use

Used for wetting and dispersion in water-based coating systems, printing inks, adhesives, water-based industrial paints and wood paints, inks, pesticides and other fields.

## • Addition amount

Inorganic pigments: 5.0%~10.0%

Organic pigments, carbon black: 20%~50%

\*. The above data are the dosage ratios in the formula(% of pigment amount). The optimal dosage needs to be determined through a series of tests.

## • Instructions for use

In order to obtain the best performance, the additives should be added to the grinding material first, and then the pigments. Premix the resin and solvent components of the grinding material, and then slowly add the additives under constant stirring. Do not add the pigment before the additives are mixed evenly.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

**Guangzhou Houhuan Chemical Auxiliary Co., Ltd.**

Tel: +86 020 82020 897

Emergency contact: +86 135 7011 0115

Factory Address: Building 30, Lot C04-01, Wanyang Industrial Park, Wengyuan County, Shaoguan City, Guangdong Province, China

E-mail: hh@gdhhx.com

Facebook: <https://www.facebook.com/profile.php?id=100055371593374>X-Twitter: <https://x.com/HHDispersants>YouTube: <https://www.youtube.com/@HH-Dispersant>Pinterest: <https://www.pinterest.com/gdhhx311>